

L2FM 定量柱塞/马达

Fixed piston motor L2FM



- 锥柱塞斜轴式定量马达，用于开式回路及闭式回路
- 输出扭矩随着高压侧和低压侧之间的压差而增大
- Fixed displacement motor with axial tapered piston rotary groups of bent-axis design, for open and closed circuits
- The torque increases with the pressure differential between the high and low pressure side and with increasing displacement

型号说明 Type code

L2F	M	107	/	6	1	W		V	Z	B	020	H	W1XA01	S
01	02	03		04	05	06		07	08	09	10	11	12	13

轴向柱塞马达 Axial piston motor

01	固定式斜轴设计 Bent-axis design, fixed displacement	L2F
----	--	-----

工作模式 Operation mode

02	马达 Motor	M
----	----------	---

规格 Size

03	排量 Vg Displacement Vg (mL/r)	45	56	63	80	90	107	125	160	107
----	------------------------------	----	----	----	----	----	-----	-----	-----	-----

系列 Series

04		6
----	--	---

索引 Index

05		1
----	--	---

旋转方向 Direction of rotation

06	从轴伸看，双向 Viewed from drive shaft, bidirectional	W
----	--	---

轴封 Shaft seal

07	氟橡胶 FKM	V
----	---------	---

轴伸 Drive shaft

		45	56	63	80	90	107	125	160
08	花键轴 DIN5480	—	●	●	●	●	●	●	—
	Splined shaft DIN5480	●	●	●	●	●	●	●	●
									A
									Z

安装法兰 Mounting flange

09	ISO 3019-2 标准法兰 4 孔	
	ISO 3019-2 Standard flange 4 hole	B

工作油口 Working ports

			45	56	63	80	90	107	125	160
02	SAE J518 法兰 A 和 B, 对侧油口 SAE J518 flange A and B, opposite side ports	0	○	●	●	●	●	●	●	○
		7	○	●	●	●	●	●	●	○
10	SAE J518 法兰 A 和 B, 底部同侧油口 SAE J518 flange A and B, same side ports at bottom	10	0	○	○	○	○	○	○	—
		17 18	1	—	—	—	—	○	○	—
				—	—	—	○	○	○	○
			0	1	7					
			不带阀 Without valve	溢流阀 With pressure-relief valves	配有冲洗阀和补油阀 With flushing and boost pressure valve					

速度传感器 Speed sensor

		45	56	63	80	90	107	125	160
11	不带转速传感器(无代码) Without speed sensor (no code)	●	●	●	●	●	●	●	
	预留 HDD 转速传感器接口 With port for HDD speed sensor	●	●	○	●	○	●	●	—
	配有 HDD 转速传感器 With HDD speed sensor	●	●	○	●	○	●	●	—

平衡阀 Counterbalance valve

12	无平衡阀 Without counterbalance valve	
	配有平衡阀 With counterbalance valve	-W1XA01

标准/特殊版本 Standard/special version

13	标准版本(无标识) Standard version (no code)	
	特殊版本 Special version	-S

技术参数 Technical data

排量 Displacement (mL/r)	额定压力 Nominal pressure (MPa)	最高压力 Max. pressure (MPa)	额定转速 Nominal speed (r/min)	最高转速 Max. speed (r/min)	重量 Weight (kg)
45	35	40	4800	5200	15
56			4400	4800	18
63					19
80			4000	4400	23
90					25
107			3600	4000	34
125			36		
160	3200	3600	47		

● = 可供货 Available ○ = 可按要求供货 On request — = 不可供货 Not available